

MUR20400CT

ULTRAFAST RECOVERY RECTIFIERS

VOLTAGE 400Volts **CURRENT** 20 Amperes


TO-220AB Unit : inch(mm)

FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-O utilizing Flame Retardant Epoxy Molding Compound.
- Exceeds environmental standards of MIL-S-19500/228
- Low power loss, high efficiency.
- Low forward voltage, high current capability
- High surge capacity.
- Ultra fast recovery times, high voltage.

MECHANICAL DATA

- Case: TO-220AB full molded plastic package
- Terminals: Lead solderable per MIL-STD-750, Method 2026
- Polarity: As marked.
- Standard packaging: Any
- Weight: 0.0655 ounces, 1.859 grams.



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

PARAMETER	SYMBOL	MUR20400CT	UNITS
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	400	v
Maximum RMS Voltage	V_{RMS}	280	v
Maximum DC Blocking Voltage	V_{DC}	400	v
Maximum Average Forward Current lead length at $T_c = 100^\circ\text{C}$	$I_{F(AV)}$	20	A
Peak Forward Surge Current : 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	150	A
Maximum Forward Voltage at 10A	V_F	1.3	v
Maximum DC Reverse Current at Rated DC Blocking Voltage $T_j=25^\circ\text{C}$ $T_j=125^\circ\text{C}$	I_R	1 500	μA
Typical Junction Capacitance (Note 1)	C_j	200	pF
Maximum Reverse Recovery Time (Note 2)	t_{rr}	35	ns
Typical Thermal Resistance (Note 3)	$R_{\theta JC}$	2	$^\circ\text{C} / \text{W}$
Operating Junction and Storage Temperature Range	T_j, T_{STG}	-65 to +150	$^\circ\text{C}$

NOTES:

1. Measured at 1 MHz and applied reverse voltage of 4.0 VDC.
2. Reverse Recovery Test Conditions: $I_F=.5A$, $I_R=1A$, $I_{rr}=.25A$.
3. Thermal resistance from Junction to ambient and from junction to lead

MUR20400CT

RATING AND CHARACTERISTIC CURVES




Fig.1 FORWARD CURRENT DERATING CURVE




Fig.2 TYPICAL JUNCTION CAPACITANCES




Fig.3 FORWARD CHARACTERISTICS




Fig.4 TYPICAL REVERSE CHARACTERISTICS




Fig.5 PEAK FORWARD SURGE CURRENT