

# MBR10100CT


## 10 AMPERES SCHOTTKY BARRIER RECTIFIERS

### FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0. Flame Retardant Epoxy Molding Compound.
- Metal silicon junction, majority carrier conduction
- Low power loss, high efficiency.
- High current capability
- Guardring for overvoltage protection
- For use in low voltage, high frequency inverters free wheeling, and polarity protection applications.
- Lead free in comply with EU RoHS 2011/65/EU directives

### MECHANICAL DATA

- Case: TO-220AB molded plastic
- Terminals: solder plated, solderable per MIL-STD-750, Method 2026
- Polarity: As marked.
- Mounting Position: Any
- Weight: 0.0655 ounces, 1.86 grams.



### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%


PARAMETER	SYMBOL	MBR10100CT	UNITS
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	100	V
Maximum RMS Voltage	$V_{RMS}$	70	V
Maximum DC Blocking Voltage	$V_{DC}$	100	V
Maximum Average Forward Current (See fig.1)	$I_{F(AV)}$	10	A
Peak Forward Surge Current : 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	$I_{FSM}$	150	A
Maximum Forward Voltage at 5A, per leg	$V_F$	0.8	V
Maximum DC Reverse Current at Rated DC Blocking Voltage	$I_R$	10 100	$\mu A$
Typical Thermal Resistance	$R_{\theta JC}$	2	°C / W
Operating and Storage Junction Temperature Range	$T_J, T_{STG}$	-65 to + 175	°C

Notes :


Both Bonding and Chip structure are available.

# MBR10100CT


## RATING AND CHARACTERISTIC CURVES




**Fig.1- FORWARD CURRENT DERATING CURVE**



**Fig.2- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTIC**



**Fig.3- TYPICAL REVERSE CHARACTERISTICS**



**Fig.4- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS**